# AX2 PIXEL BAR Coming soon

**Barndoors** Control the shape of the light

Astera ワイヤレス PIXEL BARは直線型ウォッシュライトです。各LEDは個 別にアドレス指定ができ、超高演色、デジタルカラーキャリブレーション、オリ ジナル20°ビームを提供します。スマートスタンド、吊下げブラケット、連結可能 なエンドキャップ、一体型エアラインレールにより様々な方法で素早く組み立 てられるためコンサート、ツアー、企業イベント、テレビなど様々な分野に適し ています。





Wireless DMX



## Available in 2 sizes

50cm with 8x10W and 100cm with 16x 10W (20" and 40")





Multi-functional feet with quick-release clamp



### Connector

or connecting several AX2. With IR-Module for easy communication



## **Ultra-High Color Rendering**

TLCI ≥ 96, CRI Ra ≥ 96, CRI Re ≥ 90 from 3.200K to 6.500K



## **Individually Controllable Pixels**

24

8 pixels for AX2-50 16 pixels for AX2-100



TrackPin

AX-TP

## **Airline Track**

Airline track at back and bottom to attach mounting tools



TrackHanger

AX-TH

Mounting on truss, pipes and more with TrackPin

### Safety Hook

Helps to hang AX2 safe - please check the safety regulations in your region.



## **ACCESSORIES**





**FlyBar** 

AX2-FB



## **SPECIFICATIONS**





Item Code	AX2-100 / AX2-50
Colors	RGBMintAmber
Total LED Power	160W / 80W
Power Draw	80W / 40W
Light output - 2700k, 3200k,5500k (100)*	3600lm, 4460lm, 4530lm
Light output - 2700k, 3200k,5500k (50)*	1800lm, 2230lm, 2265lm
CRI(RA)/TLCI 3200-6500k*	≥96
Strobe	0 - 25Hz
Pixels	16 (8)
Battery Lifetime	70 % after 300 cycles
Battery Runtime	up to 20 hours
Charging Time (naminal)	Elaro

Input Voltage	110 - 240V, 50/60 Hz
Range	300 m / 330 yds
Wired DMX	Yes
CRMX Receiver	Built in
Wireless Frequencies	CRMX 2.4GHz, UHF
Housing	Aluminium
IP Rating	IP65
Operating Temperature	0° - 40° C / 32° - 104° F
Weight	7.9 kg/17.5 lbs / 4.9 kg/10.8 lbs
Dimensions (mm)	1000 x 165 x 65 / 500 x 165 x 65
Dimensions (inches)	39.4 x 6,5 x 2,6 / 19.7 x 6,5 x 2,6