About BI-FLEX M7

The new BI-FLEX M7 (70W) is the cinematographer's dream come true. A small, lightweight and powerful LED light, built with our new micro LEDs.

The 70W BI-FLEX M7 is a 1'x1'(30x30cm) LED Panel. Its sleek, lightweight design makes this gadget perfect for mobile lighting or studio applications.

With the x-bender you will be able to mount the LED panel on a light stand with a 16mm (5/8) stud. The foldable and lightweight design of the x-bender ensures it will travel light and easy, inside your travel gear. You can mount a diffusor to the x-bender for a softer light.

The Dimmer is Universal up to 70W and runs from main power supply or battery.

You can use different sizes of panels with the same dimmer. The two control knobs on the dimmer give you full control over color temperature and intensity.

With the optional DMX module that can be attached to the dimmer, you are ready for a remote application. With this module it will be easy to control the color and intensity of the LED light through your 512 DMX protocol.

For even better light control we offer these accessories:

- -Softboxes for soft and even light distribution
- -Grids for the softbox for greater precision
- -A metal frame for a more solid and rugged hold
- -Snoot prevents light spill
- -Magnetic holder provides more flexibility in rigging the light.

| In the box |
|---------------------------|
| 1x BI-FLEX M7 |
| 1x Dimmer |
| 1x Stand-Mount |
| 1x Power supply 100V-240V |
| 1x Extension cable |
| 1x Diffusor |



Specifications

| · · | |
|-------------------|--------------------------------|
| Light Source | Super High CRI Power LED's 70W |
| CRI | CRI 98 / TLCI 98 |
| Color Temperature | 2900K-5600K |
| Beam Angle | 140° |
| Dimmer | Dimming: (1%–100%) |
| Cooling | passive cooling |
| Dimmer Input | 12V to 30V |
| Power Unit | Automatic Voltage 100V to 240V |
| | • |

BI-FLEX M7

| | 60cm/2ft | 1m/3ft | 2m/6ft | 3m/9ft | CRI |
|----------------|------------------|------------------|-----------------|-----------------|-----|
| Daylight 6300K | 5100 l ux | 1900 ux | 520 l ux | 260 ux | 97 |
| Bi-Color 4200K | 4900 l ux | 1810 l ux | 500 l ux | 250 l ux | 97 |
| Tungsten 2900K | 4460 l ux | 1660 l ux | 460 l ux | 225 l ux | 98 |



MFL357BIDIMVM



MFL 70BI

